

1-01							
Alimentatori monofase Single-phase loaders							
Modello Model	Potenza motore Motor power	Volume ciclone Receiver volume	Tensione/Frequenza Voltage/Frequency	Produzione oraria Max Throughput	Filtro Filter	Tubo flessibile Flex hose	Sonda aspirazione Suction wand
AM03	850 W	3 dm ³	230V/1/50-60Hz	max 40 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM04	850 W	4 dm ³	230V/1/50-60Hz	max 60 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM05	1100 W	5 dm ³	230V/1/50-60Hz	max 110 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM10	1100 W	10 dm ³	230V/1/50-60Hz	max 180 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM20	1100 W	20 dm ³	230V/1/50-60Hz	max 220 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
110V/1ph/60Hz							
AM03.60	850 W	3 dm ³	110V/1/60Hz	max 40 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM04.60	850 W	4 dm ³	110V/1/60Hz	max 60 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM05.60	1000 W	5 dm ³	110V/1/60Hz	max 110 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM10.60	1000 W	10 dm ³	110V/1/60Hz	max 180 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum
AM20.60	1000 W	20 dm ³	110V/1/60Hz	max 220 kg/h	Tessuto/ <i>Cloth</i>	L= 3 m, D=40 mm	D=40 mm, aluminum

